



TECHNOLOGIES

TELECOMMUNICATION


DT RF & Microwave Product

Low Noise Amplifier

400 to 3200 MHz

Part Number: **LNA-400-3200-SF**

Application: Cellular, PCS, Communication Receivers
& Transmitters, Satellite Communication, Military



Parameter	Min.	Typ.	Max.	Units
Gain	8	-	25	dB
Noise Figure	-	0.5	-	dB
Output P1dB	-	17	-	dBm
Output IP3	-	35	-	dBm
Input Return Loss	10	-	-	dB
Output Return Loss	17	-	-	dB
Operating Voltage	3	3.3	3.5	V
Operating Current	-	18	-	mA
Input Power	-	11	-	dBm
Operating Temperature	-40	-	85	°C
Connector Type	SMA Female			
Absolute Maximum Rating				
Source Voltage	-	+3.5	-	V
RF Input Power	-	+13	-	dBm
Storage Temperature	-45	-	95	°C







Typical Performance Curves



Input Return Loss = $-S_{11}$ (dB)

Gain (Power Gain) = S_{21} (dB)


Reverse Isolation = $-S_{12}$ (dB)

Output Return Loss = $-S_{22}$ (dB)





CAD Drawing



NOTE:

- ▶ Unless Otherwise Specified All Dimensions Are Nominal.
- ▶ All Specifications Are Subject To Change Without Notice At Any Time.
- ▶ Dimensions Are In Inches (mm).



Phone: +1(949)508 0037
Email: Sales@dioon.us

DIOON TECHNOLOGIES
WWW.DIOON.US
The Advanced Way

United States Office
660 Wald, Irvine, CA92618